

| ELEMENTY | SYMBOL | KOMINY DWUŚCIENNE, IZOLOWANE NIKO STF EDEL EKO B gr. 1,0mm, Blacha 1.4521(rdzeń); 1.4301(płaszcz) | | | | | | | | | | |
|---|--|---|-----|-----|------|------|------|------|------|------|------|------|
| | | ROZMIAR | | | | | | | | | | |
| | | 130 | 150 | 160 | 180 | 200 | 250 | 300 | 350 | 400 | 450 | 500 |
| | | 230 | 250 | 260 | 280 | 300 | 350 | 400 | 450 | 500 | 550 | 600 |
| daszek | HE-ID/śr/1,0 | 82 | 83 | 105 | 123 | 143 | 242 | 343 | 416 | 514 | 621 | 767 |
| ustnik | HE-IU/śr/1,0 | 127 | 143 | 143 | 159 | 159 | 206 | 237 | 253 | 284 | 300 | 332 |
| zakończenie izolacji | HE-IZI/śr/1,0 | 76 | 95 | 107 | 116 | 125 | 143 | 156 | 166 | 180 | 195 | 255 |
| kołnierz przecideszczowy | HE-IKP/śr/1,0 | 102 | 118 | 126 | 134 | 134 | 149 | 181 | 196 | 212 | 228 | 244 |
| plyta dachowa prosta | HE-IPDO/śr/1,0 | 102 | 118 | 126 | 134 | 134 | 149 | 181 | 196 | 212 | 228 | 244 |
| rura L=1000 | HE-IR1/śr/1,0 | 409 | 452 | 484 | 519 | 568 | 764 | 852 | 1005 | 1172 | 1506 | 1590 |
| rura L=500 | HE-IR5/śr/1,0 | 235 | 260 | 278 | 299 | 327 | 440 | 490 | 578 | 674 | 866 | 914 |
| rura L=333 | HE-IR33/śr/1,0 | 157 | 173 | 186 | 199 | 218 | 293 | 327 | 385 | 449 | 577 | 610 |
| rura L=250 | HE-IR25/śr/1,0 | 118 | 130 | 139 | 149 | 163 | 220 | 245 | 289 | 337 | 433 | 457 |
| trójnik 90° | HE-IT90/śr/1,0 | 540 | 597 | 639 | 685 | 750 | 1009 | 1124 | 1327 | 1548 | 1987 | 2099 |
| trójnik 45° | HE-IT45/śr/1,0 | 585 | 647 | 692 | 742 | 813 | 1093 | 1218 | 1437 | 1677 | 2153 | 2274 |
| wyczystka okrągła z zatyczką | HE-IWZ/śr/1,0 | 689 | 762 | 804 | 882 | 947 | 1229 | 1392 | 1609 | 1846 | 2349 | 2508 |
| wyczystka z drzwiczkami | HE-IWD/śr/1,0 | 846 | 919 | 961 | 1039 | 1104 | 1433 | 1596 | 1814 | 2050 | 2553 | 2712 |
| odskraplacz | HE-IO/śr/1,0 | 149 | 165 | 165 | 196 | 196 | 220 | 267 | 283 | 299 | 361 | 409 |
| redukcja | HE-IZR/śr/1,0 | 286 | 286 | 317 | 317 | 412 | 475 | 506 | 569 | 600 | 663 | 663 |
| kolano 60°, 90° | HE-IK60/śr/1,0;HE-IK90/śr/1,0 | 450 | 498 | 533 | 571 | 625 | 841 | 937 | 1106 | 1290 | 1656 | 1749 |
| kolano 15°, 30°, 45° | HE-IK15/śr/1,0;HE-IK30/śr/1,0;HE-IK45/śr/1,0 | 259 | 286 | 306 | 328 | 360 | 484 | 539 | 636 | 742 | 952 | 1006 |
| obejma z kątkiem | HE-IOSK/śr/1,0 | 81 | 94 | 94 | 94 | 94 | 157 | 157 | 157 | 184 | 184 | 184 |
| obejma wzmacniająca | HE-IOW/śr/1,0 | 74 | 86 | 86 | 86 | 86 | 143 | 143 | 143 | 168 | 168 | 168 |
| obejma konstrukcyjna regulowana | HE-IOS/śr/1,0 | 209 | 226 | 232 | 241 | 247 | 285 | 301 | 316 | 339 | 363 | 444 |
| plyta podstawy z odskraplaczem | HE-IPKOD/śr/1,0 | 314 | 346 | 354 | 393 | 393 | 432 | 511 | 542 | 574 | 652 | 715 |
| plyta podstawy przelotowa odciążeniowa | HE-IPKO/śr/1,0 | 205 | 233 | 248 | 265 | 275 | 339 | 390 | 424 | 469 | 536 | 588 |
| plyta podstawy przelotowa pod odskraplacz | HE-IPKODS/śr/1,0 | 205 | 233 | 248 | 265 | 275 | 339 | 390 | 424 | 469 | 536 | 588 |
| wspornik komina | HE-IWS/śr/1,0 | 252 | 284 | 301 | 323 | 345 | 409 | 561 | 676 | 775 | 877 | 1327 |
| podstawa komina fundamentowa | HE-IPKF/śr/1,0 | 314 | 346 | 354 | 393 | 393 | 432 | 511 | 542 | 574 | 652 | 715 |

| ZESTAWY KOMINÓW IZOLOWANYCH | | | | | | | | | | | |
|-----------------------------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| wysokość/średnica | 130 | 150 | 160 | 180 | 200 | 250 | 300 | 350 | 400 | 450 | 500 |
| 4 m | 3872 | 4288 | 4531 | 4912 | 5260 | 6775 | 7744 | 8969 | 10290 | 12840 | 14056 |
| 5 m | 4281 | 4740 | 5015 | 5431 | 5829 | 7539 | 8596 | 9974 | 11463 | 14346 | 15646 |
| 6 m | 4942 | 5476 | 5800 | 6274 | 6742 | 8713 | 10009 | 11655 | 13410 | 16729 | 18564 |
| 7 m | 5351 | 5929 | 6284 | 6793 | 7310 | 9477 | 10861 | 12660 | 14582 | 18234 | 20154 |
| 8 m | 6011 | 6665 | 7069 | 7635 | 8224 | 10650 | 12274 | 14341 | 16530 | 20617 | 23071 |
| 9 m | 6420 | 7117 | 7553 | 8155 | 8792 | 11415 | 13126 | 15346 | 17702 | 22122 | 24661 |
| 10 m | 6829 | 7570 | 8037 | 8674 | 9360 | 12179 | 13978 | 16351 | 18875 | 23628 | 26251 |
| 11 m | 7490 | 8306 | 8822 | 9516 | 10274 | 13353 | 15391 | 18032 | 20822 | 26011 | 29169 |
| 12 m | 7899 | 8758 | 9306 | 10036 | 10842 | 14117 | 16243 | 19037 | 21995 | 27516 | 30759 |

Komplet zawiera: ustnik, rura, trójnik 90st., wyczystka z zatyczką, płyta podstawy z odskr., podstawa komina, wspornik komina

Kontakt:

Tel: 502-423-370

E-mail:

kominy@centrumkomina.pl